



PIN	1	2	3	4	5	6	7	8	9	
COM1	COM1	1H	1A	1B	2H	2A	2B	3H	3A	
COM2		1G	1M	1K	2G	2M	2K	3G	3M	
COM3		1P	1I	1J	2P	2I	2J	3P	3I	
PIN	10	11	12	13	14	15	16	17	18	
COM1	3B	4H	4A	4B	4C	4L			3C	
COM2	3K	4G	4M	4K	4D	4D		DP	3D	
COM3	3J	4P	4I	4J	4E	4N	4F		3E	
PIN	19	20	21	22	23	24	25	26	27	28
COM1	3L		2C	2L		1C	1L			
COM2	3O		2D	2O		1D	1O			COM2
COM3	3N	3F	2E	2N	2F	1E	1N	1F		COM3

NOTES:

1. DISPLAY TYPE: TN
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: POSITIVE/REFLECTIVE
4. DRIVER METHOD: 1/3 DUTY 1/2BIAS
5. OPERATING VOLTAGE: 5.0 V
6. OPERATING TEMP: -20°C~60°C
7. STORAGE TEMP: -25°C~70°C
8. CONNECTOR: PIN



AV DISPLAY

DRAWN:
Wang

CHECKED:

APP:

LCD NO.:

DATE: 11/13/01

UNITS: MM

DWG NO.: OD-491

SHEET 1 OF 1