



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
COM1			8J		7J		6J		5J		4J		3J		2J		1J		COM1	1A	1H	2A	2H	3A	3H	4A		4H		5A	5H	6A	6H	7A	7H	8A	8H			
COM2		8F	8K	7F	7K	6F	6K	5F	5K	4F		4K		3F	3K	2F	2K	1F	1K			1B	1G	2B	2G	3B	3G	4B		4G		5B	5G	6B	6G	7B	7G	8B	8G	COM2
COM3	COM3	8E	8G	7E	7G	6E	6G	5E	5G	4E		4G		3E	3G	2E	2G	1E	1G			1C	1N	2C	2N	3C	3N	4C		4N		5C	5N	6C	6N	7C	7N	8C	8N	
COM4		8D	8L	7D	7L	6D	6L	5D	5L	4D		4L		3D	3L	2D	2L	1D	1L	COM4	1D	1M	2D	2M	3D	3M	4D		4M		5D	5M	6D	6M	7D	7M	8D	8M		

NOTES:

- 1. DISPLAY TYPE: TN
- 2. VIEWING DIRECTION: 12:00
- 3. POLARIZER MODE: POSITIVE/TRANSFLECTIVE
- 4. DRIVER METHOD: 1/4 DUTY 1/3 BIAS
- 5. OPERATING VOLTAGE: 5.0 V
- 6. OPERATING TEMP: -20°C~80°C
- 7. STORAGE TEMP: -40°C~80°C
- 8. CONNECTOR: PIN



DRAWN: Wang

CHECKED:

APP:

LCD NO.:

DATE: 03/29/01

UNITS: MM

DWG NO.: OD-894

SHEET 1 OF 1